




**STØNE**  
Don't hide it  
anymore.



**The heat pump we were  
waiting for now is here.**



STØNE vertical air delivery

STØNE





STØNE vertical air delivery







STØNE vertical air delivery





STØNE built-in







# STØNE

Don't hide it  
anymore.



# Design and integration with the building


The heat pumps currently available on the market are all characterised by a bulky and visually unpleasant outdoor unit.

They are hard to insert in a refined architectural context. It is almost impossible to imagine them in a block of flats.

STØNE originates from a new and comprehensive approach to design that blends:

- A “ground-breaking” design that demolishes existing design paradigms to merge the elements into a new and bold combination.
- Components designed and manufactured to size, of extremely high quality and capable of providing optimal performances in terms of efficiency, comfort and silence.

STØNE is an extremely advanced technological solution that is inconspicuous outdoors and optimally blends into any setting – even improving it.







## Silence and comfort

- . Air extraction from the front.
- . Plug fan inside the structure, which extracts air from the front of the unit and directs the air flow towards the heat exchange batteries.
- . The noise generated by the fan is very low and absorbed within the structure.
- . The batteries dampen the noise generated by the air flow.
- . Thanks to the vertical or horizontal flow of the delivery air, the air flow and the resulting noise can be directed towards a spot where they do not annoy, avoiding air recirculation.

 Delivery  
 Suction



# Efficiency

## A. Overturned “V” heat exchange coils


- Greater heat exchange surface
- Even distribution of air over the entire surface
- Reduced pressure loss
- Lower air flow given the same level of efficiency
- Lower air flow = greater silence during operation

## B. Heat exchange coils inside the unit

- The unit can be installed against the wall
- The coils do not get dirty and guarantee constant efficiency over time
- Faster defrosting because the heat generated does not disperse into the outside air but is used for melting the ice on the fin
- Coils with hydrophilic fin and undercooling circuit for reducing defrosting cycles and ice build-up on the base

## C. Two condensate trays

- The coil does not adhere to the tray so that condensate can be discharged effectively and rapidly
- The trays are highly inclined so that condensate can drain rapidly without icing up
- The discharge outlet of the condensate trays lies 40 cm above the ground, inside the compressor compartment which is hot



## Low-bulk installation and modularity

STØNE eliminates any unnecessary bulkiness and makes it possible to create unprecedented modular combinations, always with a minimal visual impact outdoors.





# Outdoor configurations

STØNE heat pumps can be installed also in contexts and ways that are currently unheard of. Thanks to its innovative design, STØNE can be placed entirely against the home's wall, blending elegantly into the setting. In the built-in or semi built-in version, it can disappear completely or partially into the wall.





**V**

**Exposed with vertical  
air delivery.**



**H**

**Exposed with  
horizontal air delivery.**



**IN**

**Built-in.**



**PI**

**Semi built-in.**

# STØNE

## The versions

Range:

5 kW

20 kW



### STØNE<sup>M1</sup>

Monobloc heat pump complete with pump, safety valve and expansion vessel. A compact solution that does not require any specific expertise in connecting the refrigeration lines.



### STØNE<sup>H1</sup>

An exposed tower indoor unit with integrated 200-litre storage tank for domestic hot water, connected to the outdoor unit through water connections. A complete, reliable solution with compact dimensions that does not require any specific expertise in connecting the refrigerant lines.







## STØNE<sup>B1</sup>

Indoor hydraulic module connected to the outdoor unit through refrigerant lines. A flexible solution suitable for creating tailor-made systems.



## STØNE<sup>T1</sup>

An exposed tower indoor unit with integrated 200-litre storage tank for domestic hot water, connected to the outdoor unit through refrigerant lines. A complete solution guaranteeing reliability and compact overall dimensions.



## STØNE<sup>C1</sup>

A built-in cabinet with integrated 170-litre storage tank for domestic hot water, connected to the outdoor unit through refrigerant lines. Ideal for apartments with installation in the perimeter wall.

# STØNE M1



STØNE can be used in the monobloc version, in various configurations.

This version, with hermetic monobloc cooling circuit, contains all the hydraulic devices such as, for example, the electronic pump and the expansion vessel.

The connection with the system is made through water connection.

## OUTDOOR CONFIGURATIONS

V

Exposed with vertical air delivery



H

Exposed with horizontal air delivery



IN

Built-in



PI

Semi built-in



R32

Refrigerant with low GWP for the entire range

kW

Available power range of up to 20 kW



Remote WiFi control using BUTLER (optional)


A+++

Highest energy class A+++




# Diagrams STØNE<sup>M1</sup>

1. Compressor
2. 4-way valve
3. Finned-pack heat exchanger
4. Plug fan
5. Electronic thermostatic valve
6. Brazen plate heat exchanger
7. Pump
8. Differential pressure switch
9. Expansion vessel
10. 3-bar safety valve
11. System return plumbing connection
12. System delivery plumbing connection



## Standard components




## STANDARD COMPONENTS

- A. Structure and RAL9003 panels
- B. Wall-mounting brackets
- C. Remote control panel with control interface display (supplied separately)
- D. Differential pressure switch
- E. Expansion vessel (not present in the 5M version)
- F. Primary circuit circulator pump
- G. 3-bar safety valve

## ACCESSORIES (SUPPLIED SEPARATELY)


- H. BUTLER<sup>PRO</sup> (installed in the remote electrical cabinet)
- I. BUTLER<sup>PRO TOUCH</sup>
- J. 3-way DHW valve
- K. DHW preparation tank
- L. Inertial storage tank
- M. Anti-frost safety valve

## Accessories (supplied separately)





## Installing STØNE<sup>M1</sup>



STØNE<sup>M1</sup> is a flexible solution suitable for all applications. The unit and the system are connected through plumbing connections.


STØNE<sup>M1</sup> is a heat pump that can be modular and used in cascade mode for satisfying high power levels.




- A. Roof
- B. Terrace / Balcony
- C. Wall
- D. Floor

## Example of a system

- 1. Indoor unit
- 2. Outdoor unit
- Hydraulic connections
- Domestic hot water / heating



# Diagram of STØNE<sup>M1</sup> system



A. STØNE M1 outdoor unit  
 B. 3-way valve  
 C. Thermal storage tank for instantaneous preparation of domestic hot water

D. Domestic hot water point of use  
 E. Hydraulic separator  
 F. Secondary circuit pump  
 G. Heating and cooling system

— Domestic hot water  
 — Cold water

# STONE H1

Water connection between  
the outdoor unit and the indoor unit



Tower with integrated 200-litre storage tank for domestic hot water, connected to an outdoor unit through water pipes. Not special expertise requested for installation of connections.

Ideal for houses and apartments for 4 people with normal consumption of domestic hot water.

All options are factory built in and included in the indoor unit not more need of a separate technical room.

## OUTDOOR CONFIGURATION



Exposed with  
vertical air  
delivery



Exposed with  
horizontal air  
delivery



Built-in



Semi built-in



The indoor unit has all the  
hydraulic components  
integrated into it



Production of domestic hot  
water from  $-20^{\circ}\text{C}$  to  $40^{\circ}\text{C}$   
outside air




Remote WiFi control using  
BUTLER (optional)



Highest energy class A+++




# Diagrams STØNE H1



- |  |  |  |   |
|--|--|--|---|
| A. Boiler  | 5. 3- way valve DHW system                               | 10. Domestic hot water thermostatic mixer (optional) | 16. 3-bar solar heating system safety valve (optional)        |
| B. Domestic hot water points of use                  | 6. 200-litre domestic hot water preparation storage tank | 11. Hydraulic separator (optional)                   | 17. Solar heating circuit pressure gauge (optional)           |
| C. High temperature points of use (design radiators) | 7. Hot water tank relief valve                           | 12. Secondary circuit pump (optional)                | 18. Solar heating circuit pump (optional)                     |
| D. System points of use                              | 8. DHW instantaneous heating stainless steel coil        | 13. 20-litre inertial tank (optional)                | 19. Solar heating system coil (optional)                      |
| 1. Outdoor unit                                      | 9. 7-bar domestic hot water safety valve                 | 14. Heated towel rail pump (optional)                | 20. 24-litre solar heating system expansion vessel (optional) |
| 2. 24-litre system expansion vessel                  |  | 15. Solar heating system fill valve (optional)       | 21. Solar panel   |
| 3. Filling unit                                      |  |  |   |
| 4. Y-shaped filter                                   |  |  |   |



# Standard STØNE<sup>H1</sup> components




## STØNE H1 STANDARD COMPONENTS

- A. STØNE H1 structure and RAL9003 covering panels
- B. Automatic relief valve
- C. 3-bar system safety valve
- D. 24-litre system expansion vessel
- E. System filling unit and Y-shaped filter
- F. Pressure gauge
- G. 3-way DHW system valve
- H. 200-litre domestic hot water preparation storage tank
- I. 7-bar domestic hot water safety valve
- J. Control panel with control interface display




# STØNE<sup>H1</sup> accessories supplied installed in the unit



## ACCESSORIES SUPPLIED INSTALLED IN THE UNIT

- K. BUTLER<sup>PRO</sup>
- L. Separator kit with secondary circuit pump for 5-7 kW units
- M. Separator kit with secondary circuit pump for 5-15 kW units
- N. Heated towel rail kit
- O. Solar heating kit (can be used if the inertial tank kit is not present): power pack, pump, safety valve, 24-litre expansion tank, filling unit, system fill valve, thermostatic mixer for domestic hot water and storage tank with solar coil
- P. 20-litre inertial tank kit (as an alternative to the solar kit)

## Installing STØNE<sup>H1</sup>



STØNE<sup>H1</sup> is a complete solution.

All the system's elements are contained within the cabinet, resulting in lower overall dimensions and greater reliability, since all the elements are installed, adjusted and tested at the factory.



Medium-size  
dwellings




Apartments

The indoor unit is suitable for being installed in any room thanks to its compact size and elegant forms.


- A. Kitchen / Living room
- B. Laundry room / Basement

## Example of a system

- 1. Indoor unit
- 2. Outdoor unit
- Hydraulic connections
- Domestic hot water / heating



# Diagram of STØNE<sup>H1</sup> system



- A. Outdoor unit
- B. Indoor unit
- C. Domestic hot water supply
- D. Heating system

— Domestic hot water  
— Cold water



# STONE B1

Split version with refrigerant connection between the indoor and outdoor units.



Indoor hydraulic module connected to the outdoor unit through refrigeration lines. Ideal for:

- Offices, where there is no need to produce domestic hot water.
- Villas, thanks to the combination with a domestic hot water storage tank suitably sized for satisfying high requirements.
- Multi-family central heating systems with the possibility of installing multiple units in cascade mode and the availability of domestic hot water storage tanks of suitable capacity for several users.



Indoor unit with compact dimensions. Merely 30 cm deep



Extensive power range available, up to 20 kW maximum power



Remote WiFi control using BUTLER (optional)



Highest energy class A+++

## OUTDOOR CONFIGURATION



Exposed with vertical air delivery



Exposed with horizontal air delivery



Built-in




Semi built-in




# Diagram of STØNE B1

1. Automatic relief valve
2. Electrical heater manifold (optional)
3. Plate heat exchanger
4. Differential pressure switch
5. Refrigeration connections
6. System return plumbing connection
7. System delivery plumbing connection
8. Pump
9. Pressure gauge
10. 3-bar safety valve
11. 6-litre expansion vessel

— — — Refrigeration connections



## Standard components



### STANDARD COMPONENTS

- A. Structure and RAL9003 covering panels
- B. Automatic relief valve
- C. Differential pressure switch
- D. 6-litre expansion tank
- E. Pressure gauge
- F. Primary circuit circulator pump
- G. 3-bar safety valve
- H. Control panel with control interface display


### ACCESSORIES (SUPPLIED INSTALLED ON THE UNIT)

- I. 2-4-6 kW heater kit for system and DHW (4 kW limitation for single phase heat pumps)
- J. BUTLER PRO

### ACCESSORIES (SUPPLIED SEPARATELY)

- K. 3-way DHW valve
- L. DHW preparation tank
- M. Inertial storage tank


## Accessories (supplied installed in the unit)



## Accessories (supplied separately)



# Installing STØNE B1



## INDOOR UNIT POSITION

- A. Loft
- B. Laundry room
- C. Basement

STØNE B1 is a flexible solution.

Suitable accessories are supplied depending on the application.

For large-size dwellings or blocks of flats, for example, the domestic hot water requirements can be satisfied by choosing the adequate capacity for the storage tank between 200 and 2000 litres.



Offices



Large dwellings




Central heating systems

STØNE B1 is a heat pump that can be modular and used in cascade mode for satisfying high power levels.


The indoor unit must be installed inside a room that can house all the system's components.

## Example of a central heating system

- 1. Indoor unit
- 2. Domestic hot water storage tank
- 3. Outdoor unit
- Refrigeration lines
- Domestic hot water / heating



# Diagram STØNE<sup>B1</sup>



A. Outdoor unit  
 B. Indoor unit  
 C. 3-way valve  
 D. Thermal storage tank for instantaneous preparation of domestic hot water

E. Domestic hot water point of use  
 F. Hydraulic separator  
 G. Secondary circuit pump

H. Heating and cooling system

— Domestic hot water  
 — Cold water



# STONE T1

Split version with refrigerant connection between the indoor and outdoor units.



Tower with integrated 200-litre storage tank for domestic hot water, connected to an outdoor unit through refrigerant lines.

Ideal for houses and apartments for 4 people with normal consumption of domestic hot water. All options are factory built in and included in the indoor unit not more need of a separate technical room.

## OUTDOOR CONFIGURATION

V

Exposed with vertical air delivery



H

Exposed with horizontal air delivery



IN

Built-in



PI

Semi built-in



The indoor unit has all the hydraulic components integrated into it



Production of domestic hot water from -20°C to 40°C outside air




Remote WiFi control using BUTLER (optional)



Highest energy class A+++



# Diagram STØNE T1



- A. Boiler  
B. Domestic hot water points of use  
C. High temperature points of use (design radiators)  
D. System points of use

1. Outdoor unit  
2. Plate heat exchanger  
3. Automatic relief valve  
4. 3-bar system safety valve  
5. 24-litre system expansion vessel  
6. Filling unit  
7. Y-shaped filter


8. System pressure gauge  
9. 2-4-6 kW electrical heater manifold (optional)  
10. Primary circuit pump  
11. 3-way system/DHW valve  
12. 200-litre domestic hot water preparation storage tank  
13. Hot water tank relief valve  
14. DHW instantaneous heating stainless steel coil  
15. 7-bar domestic hot water safety valve

16. Domestic hot water thermostatic mixer (optional)  
17. Hydraulic separator (optional)  
18. Secondary circuit pump (optional)  
19. 20-litre inertial tank (optional)  
20. Heated towel rail pump (optional)  
21. Solar heating system fill valve (optional)  
22. 3-bar solar heating system safety valve

- (optional)  
23. Solar heating circuit pressure gauge (optional)  
24. Solar heating circuit pump (optional)  
25. Solar heating system coil (optional)  
26. 24-litre solar heating system expansion vessel (optional)  
27. Solar panel

— — — Refrigeration connections

# Standard STØNE T1 components




## STØNE T1 STANDARD COMPONENTS

- A. Structure and RAL9003 covering panels
- B. Automatic relief valve
- C. 3-bar system safety valve
- D. 24-litre system expansion vessel
- E. System filling unit and Y-shaped filter
- F. Pressure gauge
- G. Primary circuit circulator pump
- H. 3-way DHW system valve
- I. 200-litre domestic hot water preparation storage tank
- J. 7-bar domestic hot water safety valve
- K. Control panel with control interface display




# STØNE<sup>T1</sup> accessories supplied installed in the unit



## ACCESSORIES SUPPLIED INSTALLED IN THE UNIT

- L. BUTLER PRO
- M. Separator kit with secondary circuit pump for 5-7 kW units
- N. Separator kit with secondary circuit pump for 5-15 kW units
- O. Heated towel rail kit
- P. 2-4-6 kW heater kit for system and DHW (limitation 4 kW for single-phase heat pump)
- Q. Solar heating kit (can be used if the inertial tank kit is not present): power pack, pump, safety valve, 24-litre expansion vessel, filling unit, system fill valve, domestic hot water thermostatic mixer
- R. 20-litre inertial tank kit (as an alternative to the solar kit)

## Installing STØNE T1



STØNE T1 is a complete solution.

All the system's elements are contained within the cabinet, resulting in lower overall dimensions and greater reliability, since all the elements are installed, adjusted and tested at the factory.



Medium-size dwellings



Apartments


The indoor unit is suitable for being installed in any room thanks to its compact size and elegant forms.

A. Kitchen / Living room

A. Laundry room / Basement


## Example of a system

- 1. Indoor unit
- 1. Outdoor unit
- Refrigerant
- Domestic hot water / heating





# Diagram of STØNE<sup>T1</sup> system



- A. Outdoor unit
- B. Indoor unit
- C. Domestic hot water point of use
- D. Heating system

— Domestic hot water  
— Cold water

# STONE C1

Split version with refrigerant connection between the outdoor and indoor units.




Indoor unit consisting of a cabinet to be built into the inner or perimeter wall with access to the outside through, for example, a balcony, and connected to the outdoor unit through refrigerant lines.

Ideal for apartments with 3/4 people with adequate domestic hot water consumption, thanks to the 170-litre storage tank.

Modular indoor unit with various options for satisfying all requirements of an apartment.

## OUTDOOR CONFIGURATION



Modularity, thanks to various optional modules for satisfying all the system configurations



Refrigerant with low GWP for the entire range




Remote WiFi control using BUTLER (optional)



Highest energy class A+++



# Diagram STØNE C1



A. Domestic hot water points of use  
B. Points of use

1. Outdoor unit
2. Plate heat exchanger
3. Automatic relief valve
4. 3-bar system safety valve
5. 8-litre system expansion vessel
6. Filling unit
7. Y-shaped filter


8. System pressure gauge
9. 2-4-6 kW electrical heater manifold (optional)
10. Primary circuit pump
11. 3-way system/DHW valve
12. 170-litre domestic hot water storage tank
13. Hot water tank relief valve
14. 4-litre expansion vessel
15. 7-bar domestic hot water safety valve

16. Domestic hot water thermostatic mixer
17. Inertial storage tank / 30-litre hydraulic separator (optional)
18. Secondary circuit pump (optional)
19. Secondary circuit pump and mixing valve (optional)
20. Solar heating system fill valve (optional)

21. 3-bar solar heating system safety valve (optional)
22. Solar heating circuit pressure gauge (optional)
23. Solar heating circuit pump (optional)
24. Solar heating system expansion vessel (optional)
25. Solar panel

— — — Refrigeration connections

# Standard STØNE<sup>C1</sup> components




## STANDARD COMPONENTS

- A. Casing with doors on the front
- B. 170-litre domestic hot water storage tank
- C. Hydronic module
- D. Automatic relief valve
- E. Differential pressure switch
- F. Primary circuit circulator pump
- G. 3-bar safety valve
- H. 8-litre expansion vessel
- I. Control panel with control interface display
- J. System filling unit and Y-shaped filter
- K. 3-way DHW system valve
- L. 7-bar domestic hot water safety valve
- M. 4-litre domestic hot water expansion vessel



# STØNE<sup>C1</sup> accessories supplied separately




## ACCESSORIES KIT

- N. 30-litre inertial storage tank
- O. 30-litre hydraulic separator kit and control board for the secondary circuit pumps kit
- P. Secondary circuit pump kit
- Q. Secondary circuit pump+mixing valve kit
- R. Solar heating kit: power pack, pump, safety valve, filling unit expansion vessel, domestic hot water thermostatic mixer
- S. 2-4-6 kW heater kit for system and DHW (limitation 4 kW for single-phase heat pump)
- T. BUTLER<sup>PRO</sup>



## Installing STØNE C1



STØNE C1 is a flexible solution with various modules that can be installed also at a later stage, depending in the system's configuration.



Medium-size dwellings




Apartments


The unit's casing is fitted into the wall recess during the masonry works. The casing includes the hydraulic fittings for connection to the system. The various modules are installed subsequently, once the system has been completed.

- A. Landing of the apartment
- A. Laundry room
- A. Terrace / Balcony


## STØNE C1 installation phases



1. Positioning of the casing to be recessed into the wall.



2. Connections to the system from three different positions: from the rear, side and below.




3. Install the internal components and make the relative connections.




## Example of a system

- 1. Indoor unit
- 2. Outdoor unit
- Refrigerant
- Domestic hot water / heating



## Diagram of STØNE<sup>C1</sup> system




- A. Outdoor unit
- B. Indoor unit
- C. Domestic hot water point of use

- D. Heating and cooling system

- Domestic hot water
- Cold water


## Position of STØNE connection

The input for the electronic, hydraulic (STØNE M1 e H1) or refrigeration connections (STØNE B1, T1, C1) are on the rear or lower side of the STØNE.



## Distances between components

STØNE splitted version B1 - T1 - C1



## Dimensions STØNE M1 - H1



**STØNE exposed with vertical air delivery**

		M1-H1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	1089	1089	1343	1343	1343	1539	1539	1539	1539
Height	mm	924	924	1089	1089	1089	1442	1442	1442	1442
Depht	mm	321	321	348	348	348	407	407	407	407
Net weight	Kg	120	120	134	140	140	154	154	160	160



**STØNE exposed with horizontal air delivery**

		M1-H1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	1089	1089	1343	1343	1343	1539	1539	1539	1539
Height	mm	1151	1151	1316	1316	1316	1649	1649	1649	1649
Depht	mm	321	321	348	348	348	407	407	407	407
Net weight	Kg	125	125	140	145	145	160	160	165	165



**STØNE built-in**

		M1-H1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	1089	1089	1343	1343	1343	1539	1539	1539	1539
Height	mm	1151	1151	1316	1316	1316	1649	1649	1649	1649
Depht	mm	333	333	358	358	358	415	415	415	415
Net weight	Kg	110	110	120	125	125	140	140	145	145



**STØNE semi built-in**

		M1-H1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	1089	1089	1343	1343	1343	1539	1539	1539	1539
Height	mm	1151	1151	1316	1316	1316	1649	1649	1649	1649
Depht	mm	333	333	358	358	358	415	415	415	415
Net weight	Kg	110	110	120	125	125	140	140	145	145

# Dimensions of the outdoor units **STØNE<sup>B1</sup>, STØNE<sup>T1</sup>, STØNE<sup>C1</sup>**

## STØNE exposed with vertical air delivery



		B1 - T1 - C1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	972	972	1226	1226	1226	1423	1423	1423	1423
Height	mm	924	924	1089	1089	1089	1422	1422	1422	1422
Depht	mm	321	321	348	348	348	407	407	407	407
Net weight	Kg	100	100	113	119	119	133	133	139	139

## STØNE exposed with horizontal air delivery



		B1 - T1 - C1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	973	973	1226	1226	1226	1423	1423	1423	1423
Height	mm	1151	1151	1316	1316	1316	1649	1649	1649	1649
Depht	mm	321	321	348	348	348	407	407	407	407
Net weight	Kg	105	105	118	123,5	123,5	138	138	143,5	143,5

## STØNE built-in



		B1 - T1 - C1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	1089	1089	1343	1343	1343	1539	1539	1539	1539
Height	mm	1151	1151	1316	1316	1316	1649	1649	1649	1649
Depht	mm	333	333	358	358	358	415	415	415	415
Net weight	Kg	90	91	101	106	106	121	121	126	126

## STØNE semi built-in



		B1 - T1 - C1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	1089	1089	1343	1343	1343	1539	1539	1539	1539
Height	mm	1151	1151	1316	1316	1316	1649	1649	1649	1649
Depht	mm	333	333	358	358	358	415	415	415	415
Net weight	Kg	90	91	101	106	106	121	121	126	126





# Dimensions of the indoor units

## STØNE <sup>B1</sup>, STØNE <sup>H1-T1</sup>, STØNE <sup>C1</sup>



### STØNE B1

		B1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	501	501	501	501	501	501	501	501	501
Height	mm	825	825	825	825	825	825	825	825	825
Depht	mm	321	321	321	321	321	321	321	321	321
Net weight	Kg	41	41	41	41	41	43	43	43	43



### STØNE H1 - T1

		H1 - T1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	600	600	600	600	600	600	600	600	600
Height	mm	2000	2000	2000	2000	2000	2000	2000	2000	2000
Depht	mm	600	600	600	600	600	600	600	600	600
Net weight	Kg	172	172	172	172	172	172	172	172	172




### STØNE C1


		C1								
SIZES		5M	7M	9M	11M	11T	13M	13T	15M	15T
Widht	mm	950	950	950	950	950	950	950	950	950
Height	mm	2201	2201	2201	2201	2201	2201	2201	2201	2201
Depht	mm	358	358	358	358	358	358	358	358	358
Net weight	Kg	172	172	172	172	172	172	172	172	172

# Installation distances


## STØNE exposed with top air delivery V



## STØNE exposed with front air delivery H




## STØNE built-in IN and semi built-in PI




# Multiple installation

## Ground installation



## Wall installation



\* Split version 200 mm

# Technical datas sheets

TECHNICAL DATAS		STØNE M1 - H1 - B1 - T1 - C1								
	u.m.	5M	7M	9M	11M	11T	13M	13T	15M	15T
<b>HEATING PERFORMANCES (A7°C BS; W35°C)</b>										
Max heat power (1)	kW	7,54	10,75	11,45	13,53	13,53	15,20	15,20	19,05	19,05
Nominal heat power (1)	kW	5,51	7,46	9,12	10,63	10,63	12,48	12,48	15,15	15,15
Total absorbed power (1)	kW	1,16	1,62	1,83	2,37	2,37	2,62	2,62	3,23	3,23
COP (1)		4,74	4,43	4,67	4,48	4,48	4,76	4,76	4,70	4,70
SCOP (5)		4,55	4,22	4,52	4,25	4,25	4,68	4,68	4,53	4,53
Energy efficiency class (5)		A+++	A++	A+++	A++	A++	A+++	A+++	A+++	A+++
<b>HEATING PERFORMANCES (A-7°C BS; W35°C)</b>										
Max heat power (2)	kW	4,85	6,45	7,05	7,88	7,88	9,05	9,05	11,42	11,42
Total absorbed power (2)	kW	1,62	2,26	2,38	2,91	2,91	2,87	2,87	3,91	3,91
COP (2)		2,98	2,85	2,95	2,70	2,70	3,15	3,15	2,92	2,92
<b>COOLING PERFORMANCES (A35°C; W18°C)</b>										
Nominal cooling power (3)	kW	9,20	11,55	13,05	14,35	14,35	16,90	16,90	20,50	20,50
Nominal cooling power (3)	kW	6,90	9,50	10,50	12,15	12,15	13,05	13,05	17,45	17,45
Total absorbed power (3)	kW	1,59	2,25	2,44	2,87	2,87	2,96	2,96	4,04	4,04
EER (3)		4,33	4,23	4,31	4,23	4,23	4,41	4,41	4,32	4,32
<b>COOLING PERFORMANCES (A35°C; W7°C)</b>										
Max cooling power (4)	kW	6,70	8,85	9,50	11,15	11,15	12,45	12,45	15,90	15,90
Nominal cooling power (4)	kW	4,19	6,44	7,78	8,78	8,78	9,98	9,98	12,04	12,04
Total absorbed power (4)	kW	1,22	2,00	2,33	2,65	2,65	2,99	2,99	3,71	3,71
EER (4)		3,43	3,22	3,34	3,31	3,31	3,34	3,34	3,24	3,24
<b>HYDRAULIC DATA</b>										
Nominal flow rate in heating (A7/W35 °C) (1)	l/min	15,9	21,5	26,3	30,6	30,6	35,9	35,9	43,6	43,6
Nominal flow rate in cooling (A35/W7 °C) (4)	l/min	11,7	18,6	22,4	25,3	25,3	28,9	28,9	34,9	34,9
M1-H1-B1 available pressure primary circuit	kPa	71	60	54	70	70	60	60	58	58
T1-C1 available pressure primary circuit	kPa	71	60	54	45	45	40	40	43	43
Diameter of hydraulic fittings	" GAS	1"								
M1 expansion vessel capacity	L	2	2	4	4	4	6	6	6	6
B1 expansion vessel capacity	L	6								
H1-T1-C1 expansion vessel capacity	L	24								
Minimum system water content	L	20	25	30	35	35	40	40	50	50
H1-T1 tank capacity	L	200								
C1 tank capacity	L	170								



TECHNICAL DATAS			STØNE M1 - H1 - B1 - T1 - C1							
	u.m.	5M	7M	9M	11M	11T	13M	13T	15M	15T
REFRIGERATOR FITTINGS (versioni B1 - T1 - C1)										
Aspiration	“ SAE	5/8"								
Liquid	“ SAE	3/8"								
REFRIGERATION CIRCUIT										
Compressor		Twin Rotary DC Inverter								
Refrigerant charge R32 M1	kg	1,8	1,8	2,8	2,8	2,8	3,8	3,8	3,8	3,8
Refrigerant charge R32 B1-T1-C1	kg	1,8	1,8	2,7	2,7	2,7	3,8	3,8	3,8	3,8
SOUND DATA										
Outdoor unit sound pressure Cooling/Heating 50% of the load (6)	dB(A)	45	47	48	49	49	47	47	51	51
Sound pressure external Cooling/Heating unit (7)	dB(A)	48	49	50	52	52	50	50	54	54
Sound pressure internal unit (7)	dB(A)	30	30	30	31	31	31	31	31	31
ELECTRICAL DATA										
Power Supply	V/50Hz	230/1/50	230/1/50	230/1/50	230/1/50	400/3/50	230/1/50	400/3/50	230/1/50	400/3/50
Max power input	kW	2,9	3,8	4,5	5,3	5,3	5,9	5,9	7,3	7,3
Max current absorbed	A	14,00	18,00	21,30	25,00	8,50	28,00	9,30	34,50	11,50
Indoor unit protection degree		IPX2								
Degree of protection outdoor unit		IPX4								

(1) In/Out. water T 30/35 °C; Outside air T 7 °C; R.H. 85%

(2) In/Out. water T 30/35 °C; Outside air T -7 °C

(3) In/Out. water T 23/18 °C; Outside air T 35 °C

(4) In/Out. water T 12/7 °C; Outside air T 35 °C

(5) Seasonal efficiency according to UNI 14825. Energy Efficiency Class referred to the climatic profile  
Average for flow temperature of 35 °C in compliance with regulation 811/2013

(6) Sound pressure at a distance of 1 metre in open field with compressor in 50% load modulation


(7) Sound pressure at a distance of 1 metre in open field at rated power

Rated performances as per the UNI EN 14511 standard


The performance data indicated may be subject to change



## Heating and domestic hot water



## Cooling





# BUTLER PRO, advanced control of the system

The BUTLER<sup>PRO</sup> web server is the system that INNOVA has developed to control an entire winter and summer air conditioning system from a local and remote network. BUTLER<sup>PRO</sup> allows you to connect the heat pump, controlled mechanical ventilation system, fan coils and all the other system elements via a serial connection. BUTLER<sup>PRO</sup> is complete, simple and intuitive at the same time: you can configure a weekly calendar with time zones, create specific zones and change the settings so your home is at the right comfort level for your needs.


## TWO VERSIONS

### BUTLER<sup>PRO</sup>

settings and display via smartphone / tablet / computer only with internet connection. Installation on a 35 mm DIN rail in the electrical cabinet of the heat pump or in the electrical cabinet of the house.


### BUTLER<sup>PRO</sup> TOUCH

settings and display via the integrated 10" touch screen. Can be connected to the internet remotely via smartphone / tablet / computer. Recessed wall installation. The pre-installation box is supplied separately.



## ROOM-BASED CONTROL

You can control each room with BUTLER<sup>PRO</sup> by configuring a weekly calendar with time zones, creating settings for each room or area, modifying the settings so your home is at just the right comfort level for your needs.



## MAIN FUNCTIONS

- **Supervision and control through local network or remotely**

The system can be managed through a smartphone, tablet or computer

- **Summer and winter personalised programming**

Different programmes can be set for each season

- **Setting of three temperature levels on the INNOVA fan coil network**

For each room or zone it is possible to select 3 different work temperatures, which can be modified at any time

- **Weekly time programming**


In each room it is possible to set different operating times

- **Etwork interface like the one on PCs**

Once the bus network between the heat pump and the fan coils has been made, the connection with the Web server is the same as that of a normal computer

- **Remote assistance**

With the user's consent, BUTLER can automatically access the INNOVA cloud for diagnostics and assistance in case of need



- A** WEEKLY SCHEDULING
- B** DOMESTIC HOT WATER SETTINGS







## Remote assistance


With the user's consent, BUTLER can automatically access the INNOVA cloud for diagnostics and assistance in case of need. Thanks to the Internet connection, it is possible to verify remotely the correct operation of INNOVA products connected to the BUTLER.

Any operating anomalies can be transmitted automatically from the BUTLER to the assistance centre which can intervene by modifying the functional parameters or decide to physically intervene by providing a quick and timely service.




## Total control

The advantage of choosing a complete INNOVA system is that, for any need, we are the only reference both for routine maintenance and for assistance purposes. A complete and high quality service.



INNOVA HRA -i  
HEAT RECOVERY VENTILATION  
with thermodynamic heat recovery



# What is a heat pump?

A refrigerator does not cool: it removes heat from a low-temperature environment and transfers it to a warmer environment.


A heat pump works with the same principle: it removes heat from a cool outdoor environment and transfers it to a warmer indoor environment.

The cycle can be inverted during summer, as indoor environments can be cooled by releasing the heat towards the outside.

This process uses thermal energy already present in nature.





A heat pump needs electricity to activate but it produces heat by absorbing energy from outside sources: air, water or, in the case of geothermal systems, the ground.

If the electricity is generated by a photovoltaic system or by wind turbines, the thermal energy produced is entirely free and renewable.





## Comparison between a boiler and a heat pump

	ENERGY REQUIRED	ENERGY PRODUCED BY A BOILER	ENERGY PRODUCED BY THE HEAT PUMP	
 HEATING	10 kWh	1,75 €	0,90 €	-50 %
 DOMESTIC HOT WATER (DHW)	1,3* kWh	0,23 €	0,14 €	-40 %
 RENEWABLE ENERGY		0	4,6 kWh	100 %
 EMISSIONS		2,68 kg CO <sub>2</sub>	1,25 kg** CO <sub>2</sub>	-50 %


\* daily energy requirements of a person = 50 litres of hot water at 40°C

\*\* indirect CO<sub>2</sub> emissions produced by the national electricity production system

1 kWh = 0.4332 kg of CO<sub>2</sub>



## Efficiency of a Heat pump Inverter vs on/off



**COP:** represents the power supplied and the power absorbed

The requirement of a building is maximum at the design temperature and decreases linearly as the outside temperature increases.

The heat pump with inverter compressor adjusts the power supplied on the basis of the building's requirements.

The higher the outside temperature the lower the power supplied and, consequently, the higher the efficiency.

The heat pump with on/off compressor always works at 100% and, the higher the outside temperature the higher the power generated, conversely to the building's requirements. In these conditions, to satisfy the requested load the compressor works with repeated stops and starts, which sensibly reduce its efficiency.



## Energy saving

The INNOVA DC Inverter heat pumps ensure considerable energy saving both during heating and when producing domestic hot water, thanks to their high SCOP (Seasonal Coefficient of Performance). Compared to a boiler, the heating cost for the entire winter season can be 30/50% lower.



radiators

dal 30% → al 50%



radiant panels





STØNE vertical air delivery



STØNE semi built-in



STØNE horizontal air delivery





STØNE vertical air delivery



STØNE built-in



STØNE vertical air delivery



STØNE built-in







STØNE built-in





STØNE horizontal air delivery

## CREDITS

Product Designer  
Luca Papini

Art Direction & Graphic  
Federico Castelli

Photography  
Ottavio Tomasini

Special thanks to:  
Akira Nishikawa

© All rights reserved - photographs, images and texts are protected by copyright, any use of all or part of them not expressly authorised by INNOVA will result in consequent sanctions.

INNOVA reserves the right to make changes at any time to its products, accessories and technical data in order to improve its offer.



STØNE vertical air delivery





Ideas  
that become  
reality.





**INNOVA s.r.l.**  
Via 1° Maggio, 8  
38089 Storo (Tn)  
Tel. +39 0465 670104  
Fax: +39 0465 674965  
[info@innovaenergie.com](mailto:info@innovaenergie.com)

[www.innovaenergie.com](http://www.innovaenergie.com)

Edition 2022/1